

FK FUKU 福客®

顶峰

我们 伫立在行业的
We stand at the height of industry



FK14-160T
进取不止



Basic Information

Operating weight
17T

Dozing capacity
4.55m³

Blade width
3390mm

Max. torque
830N.m

Rated power
131KW

Gradeability
30°



Technical Specification



Outline

Model	FK14-160T
Engine model	Weichai WD10G178E25
Displacement (L)	9.726
Rated power (kw/rpm)	131/1850
Max.torque (N.m/rpm)	830/1000-1200
Operating weight	17T
Dimension(no ripper)(mm)	5140×3388×3032
Min ground clearance(mm)	405
Ground pressure(MPa)	0.067
Track gauge (mm)	1880
Dozing capacity(m ³)	4.55
Blade width (mm)	3390
Blade height(mm)	1150
Max drop below ground (mm)	540
Track shoe width (mm)	510
Pitch (mm)	203.2
Quantity of track link	37
Quantity of Carrier rollers	4
Quantity of Track rollers	12 (8 Double+4 Single)
Max pressure (MPa)	14
Discharge (L/min)	213
Max tractor force (KN)	146
Grade ability	30°
Gear 1st speed (km/h)	3.29
Max speed (km/h)	9.63
Main clutch force (N)	145
Steering clutch force (N)	80
Mechanical transmission force (N)	112
Hydraulic transmission force (N)	46
Product Features	Excellent efficiency Booster Car air conditioner Protective Device GPS positioning

